

PVC
3 1/4"

DOUBLE HUNG



PVC 3 1/4"

DOUBLE HUNG

CHARACTERISTICS

1. Multi-chamber welded PVC frame for better insulation.
2. Strong PVC welded sash.
3. Virgin PVC extruded profiles provide a glossy finish and facilitate cleaning.
4. Integrated handle on the sashes.
5. Sashes can be tilted to facilitate easy cleaning.
6. Full overlapping screen for bug free ventilation, easy removal and a clean look.
7. 3/4" integrated return groove for multiple jamb options.



OPTIONS

- A. Multitude of interior or exterior mouldings.
- B. Double or triple glazing.
- C. Various internal grille shapes, colour and patterns along with external mounted SDL grilles.
- D. Self engaging lock system.
- E. Premium vent control stop.

PERFORMANCES

	NAFS-08	CSA A440-00
Air filtration/exfiltration:	A3	A3
Water resistance:	40/90	B3/B6
Design Pressure:	DP50/DP55	C3/C4
Primary designator:	R-PG40 1600 x 1100 (63x43) Type HS	R-PG55 1600 x 1100 (63x43) Type HS



Self Engaging Lock



Vent Control Stop



Brantford: 519-753-3939
Kitchener: 519-569-8700
Hamilton: 905-972-9988
Oakville: 905-567-5900
Toll Free: 866-757-1241



76 Middleton St, Brantford, ON, N3S 7V7
info@caymanwindows.com
www.caymanwindows.com