

PVC
3 1/4"

SINGLE HUNG



PVC 3 1/4"

SINGLE HUNG

CHARACTERISTICS

1. Multi-chamber welded PVC frame for better insulation.
2. Strong PVC welded sash.
3. Virgin PVC extruded profiles provide a glossy finish and facilitate cleaning.
4. Integrated pullrail on the sash.
5. Operating sash can be tilted to facilitate easy cleaning.
6. Half screen for unobstructed view.
7. 3/4" integrated return groove for multiple jamb options.

OPTIONS

- A. Multitude of interior or exterior mouldings.
- B. Double or triple glass.
- C. Various internal grille shapes, colours and patterns along with external mounted SDL grilles.
- D. Self engaging lock system.

PERFORMANCES

	NAFS-08	CSA A440-00
Air filtration/exfiltration:	A3	A3/F
Water resistance:	40/85	B3/B6
Design Pressure:	DP85/DP95	C3/C5
Primary designator:	R-PG40 1000 x 1600 (39x63) Type H	R-PG85 1000 x 1600 (39x63) Type H



Self Engaging Lock



Brantford: 519-753-3939
Kitchener: 519-569-8700
Hamilton: 905-972-9988
Oakville: 905-567-5900
Toll Free: 866-757-1241



76 Middleton St, Brantford, ON, N3S 7V7
info@caymanwindows.com
www.caymanwindows.com